



## **NLB3 Bulldozer Tires**

The Duratech NLB3 is a classical multi-purpose tread pattern designed for wheel loaders, dozers, graders, etc. NLB3 perfectly satisfies a balance of excellent traction, stability and extended wear life. And this makes it a perfect OE tire choice for some of the biggest loader manufacturers.



### **Parts Details Of NLB3 Bulldozer Tires**

#### **Classical non-directional pattern with big tread width:**

- The non-directional tread design enables excellent traction in both directions.
- The NLB3 is designed with big tread width, which offers better comfort, stability and flotation.



## More rubber built in and exclusive compounds for better resistance to cuts and wear:

- 10% more rubber built in compared with competitors and wear life is increased proportionately.
- Exclusive compounds applied to provide excellent resistance to heat generation, cuts and wear.

## Robust carcass design and lugs reinforced by a centerpiece tread belt

- NLB is built with robust carcass and a strengthened centerpiece tread belt, which make the tire well adapted to even the worst applications.

## Specifications of NLB3 Bulldozer Tires

Size	Ply Rating	TRA Code	Rim	Dimension		Load Capacity		Inflation Pressure		Tread Depth-mm	Type
				Section width-mm	Overall diameter-mm	10km/h	50km/h	10km/h	50km/h		
17.5-25	12	L-3/G-1	14.00/1.5	445	1350	6150	3650	350	225	26	TT/TL
17.5-25	16	L-3/G-1	14.00/1.5	445	1350	7300	4250	475	300	26	TT/TL
17.5-25	20	L-3/G-1	14.00/1.5	445	1350	8250	5000	575	400	26	TT/TL
20.5-25	16	E-3/G-1	17.00/2.0	520	1490	8250	5450	350	275	28	TT/TL
20.5-25	20	E-3/G-1	17.00/2.0	520	1490	9500	6000	450	325	28	TT/TL
23.5-25	16	L-3/G-1	19.50/2.5	595	1615	9500	6150	300	225	33.5	TT/TL
23.5-25	20	L-3/G-1	19.50/2.5	595	1615	10900	7300	375	300	33.5	TT/TL
23.5-25	24	L-3/G-1	19.50/2.5	595	1615	12500	8000	475	350	33.5	TT/TL
26.5-25	20	E-3/L-3	22.00/3.0	675	1750	13200	8250	350	250	39	TT/TL
26.5-25	24	E-3/L-3	22.00/3.0	675	1750	14000	9250	400	300	39	TT/TL



## Duratech Industrial (Jinan) Co., Ltd

26.5-25	28	E-3/L-3	22.00/3.0	675	1750	15500	10000	475	350	39	TT/TL
16/70-20	14	E-3/L-3	13 (SDC)	410	1075	5150	2900	450	350	25	TT/TL
16/70-20	18	E-3/L-3	13 (SDC)	410	1075	5800	3350	550	450	25	TT/TL
20.5/70-16	14	E-3/L-3	10.00F	365	950	1600	/	280	/	17	TT
16/70-24	14	E-3/L-3	13 (SDC)	410	1175	5600	3350	450	350	25	TT
8.25-16	14	E-3/L-3	6.50H	235	865	2300	/	800	/	15	TT
18/90-16	14	E-3/L-3	16×10/8	220	885	1560	/	280	/	15	TT