

## RL31N

L-3/E-3



### SUPERIOR TRACTION AND STABILITY; LONG LASTING PERFORMANCE

- **Non-directional multiblock tread pattern and open shoulder grooves; Ultra-wide tread**

Benefit: To provide superior traction and stability.

- **Double-reinforcement tie-bars**

Benefit: To deliver better center-block strength and improved wear resistance.

- **High tensile steel belt package built in**

Benefit: To resist impacts and minimize damages.

- **Super thick tread base and thickened sidewalls.**

Benefit: Better cut and puncture resistance.



Size	Star Rating	TRA Code	Rim	Section width		Overall Diameter		Tread Depth	Load Index & Speed Symbol	Standard Inflation Pressure (kPa)	Type
				in	mm	in	mm				
17.5R25	★★	L-3/E-3	14.00/1.5	17.52	445	53.14	1350	28	182A2/167B	600	TL
20.5R25	★★	L-3/E-3	17.00/2.0	20.47	520	58.66	1490	32	193A2/177B	600	TL
23.5R25	★★	L-3/E-3	19.50/2.5	23.43	595	63.58	1615	35	201A2/185B	600	TL
26.5R25	★★	L-3/E-3	22.00/3.0	26.57	675	68.90	1750	40	209A2/193B	600	TL
29.5R25	★★	L-3/E-3	25.00/3.5	29.53	750	73.74	1875	40	216A2/200B	600	TL