

UTS6

E-4



STRONGER TIRE FOR SURFACE MINING, EXCEPTIONAL TIRE LIFE

- Extra wide tread, tough lugs and deep tread depth**
Benefit: Greater ground contact, stability and traction.
- Special groove design: added slanted grooves; deep main grooves and shallow sub grooves combined**
Benefit: Enhanced grip, improved lateral traction, better wear resistance when the grooves go shallow.
- Reinforced tire structure: six layers of steel belts, robust carcass, new structure ply cord and lengthened ply cord wrapping-up**
Benefit: Extra impact resistance and load capacity.



Size	Star Rating	TRA Code	Rim	Section width		Overall Diameter		Tread Depth		Load Index & Speed Symbol	Standard Inflation Pressure (kPa)	Type
				in	mm	in	mm	32nds	mm			
18.00R25	★★	E3	13.00/2.5	19.84	504	63.9	1623	40	32	185B	700	TL
18.00R33	★★	E4	13.00/2.5	17.52	515	55.08	1858	69	55	191B	700	TL
21.00R35	★★	E4	15.00/3.0	20.51	590	60.94	2032	69	55	201B	700	TL
24.00R35	★★	E4	17.00/3.5	25.71	653	85.04	2160	79	63	209B	700	TL
27.00R49	★★	E4	19.50/4.0	29.06	738	105.31	2675	82	65	223B	700	TL
30.00R51	★★	E4	22.00/5.0	32.48	825	113.66	2887	97	77	230B	700	TL
33.00R51	★★	E4	24.00/5.0	35.87	911	119.96	3047	120	95	235B	700	TL